

1. Remove the original step (and the light shroud on the 88 series tractor.)

**NOTE: A section of the shroud must be cut off as shown below.  
(Flatten tin strip under door.)**

2. Fasten the **mounting bracket** to the side of the tractor cab with two 3/8" x 1 1/2" carriage bolts, flat washers, lock washers and nuts. Use the original bolts in the bottom and rear holes.
3. Place a 3/8" x 1 1/2" carriage bolt in either of the two slotted holes in the bottom of the **mounting bracket**.

**NOTE: Your choice will determine the location of the step in relation to the wheel.**

Use this bolt and a 1/2" x 3 1/2" bolt to fasten the **top step section** to the **mounting bracket**. On the 88 series, place the metal **battery shield** provided with the step between the **mounting bracket** and the battery support straps.

4. Slide the **bottom step section** between the side plates of the **top step section**.
5. Position the **middle step** so it is equally spaced between the **top** and **bottom step sections**. Equal spacing can also be achieved if the **optional fourth step** is being used. Secure with four 3/8" x 1" carriage bolts, flat washers, lock washers and nuts. If using the **optional fourth step**, fasten it with four 3/8" x 3/4" bolts, flat washers, lock washers and nuts.

6. Fasten the lower end of the **handrail** to the rear side of the **mounting bracket** with two 3/8" x 1" bolts, flat washers, lock washers and nuts.
7. Clamp the upper end of the **handrail** to the front side of the fender and drill two 5/16" holes. Fasten using two 5/16" x 1" bolts, lock washers and nuts.

