

POLY TECH INDUSTRIES, INC.

P.O. Drawer 349. Monticello, GA 31064 Phone: 800-542-7659 Fax: 706-468-2881 Email: polytech@polyskid.com www.polyskid.com

Grain Grabber Mounting Instructions:



1. To begin, roll auger in direction of travel until outer end flight beginning point is at 12 o'clock noon.

NEXT: Place first Grain Grabber2 on auger tube halfway between where the flight begins and the next auger flight.

The Grain Grabber2 is designed with a curve which fits snug against the auger tube. Mark hole placements.

Drill holes with the drill bit, included in your kit, to ensure that the self tapping screws will hold tight. Attach Grain Grabber2 with the self-tapping bolts included in your kit.



2. To install the second Grain Grabber2, roll the auger backwards, (towards the combine) onequarter turn.

NEXT: Place second Grain Grabber2 on auger tube halfway between the next two flightings at 12 o'clock noon. Mark hole placements.

Drill holes with the drill bit, included in your kit, to ensure that the self tapping screws will hold tight. Attach Grain Grabber2 with the self-tapping bolts included in your kit.



3. To install the third Grain Grabber2, roll the auger backwards (towards the combine) again one-quarter turn.

NEXT: Place second Grain Grabber2 on auger tube halfway between the next two flightings at 12 o'clock noon. Mark hole placements. Drill four holes with the drill bit, included in your kit, to ensure that the self tapping screws will hold tight. Attach Grain Grabber2 with the self-tapping bolts included in your kit.

per side. Owners of 20' grain heads may

The 20' grain head requires 3 Grain Grabber2 have additional flights before the retractable fingers which do not have a Grain Grabber2.







Owners of grain heads wider than 20' only, please continue to the next step.

- 4. To install the fourth Grain Grabber2 (for 25' and 30' heads only) roll the auger backwards, (towards the combine) again onequarter turn. Repeat NEXT: step, yet the placement will be between the next two flightings at 12 o'clock noon.
- 5. To install the fifth Grain Grabber2 (for 30' heads only) roll the auger backwards, (towards the combine) again one-quarter turn. Repeat NEXT: step, yet the placement will be between the next two flightings at 12 o'clock noon. .

In short, each additional Grain Grabber2 will be installed after a one-quarter turn of the auger in the opposite direction of travel.