



Easy Greasing is Thorough Greasing

## Technical Specification Sheet

### LOCK N LUBE<sup>®</sup> - GREASE GUN COUPLER

#### Spring Loaded Activation Trigger

- Simply depress the trigger when locking the coupler onto the Zerk or to release the coupler when done.
- Easy clip-off, regardless of pressure build up in the line. NO MORE stuck couplers.
- No need to hold while greasing. Lock-on and free up both hands to operate your grease gun.

#### Sliding Sleeve

Locks the coupler onto the Zerk.  
When you pump grease ... it stays on!



#### 1/8" NPT Female Thread

Standard size, fits most grease guns.



#### Four hardened spring steel jaws

Resilient under high pressure.  
Fits all DIN and SAE specification Zerk grease nipples.

#### Leak Free, High Pressure Seal

Patented design reduces leakage.

## Technical Specifications

Description	Specification
Max Pressure	10,000 psi (690 Bar)
Zerk Compatibility	Fits all DIN and SAE specification Zerks (grease nipples).
Coupler Thread	1/8" NPT female thread.
Dimensions	L: 3 1/2 x W: 3/5 x H: 1 3/5 In (L: 88 x W: 16.4 x H: 41 mm)
Diameter (front coupler)	3/8 in (16 mm). Fits most recessed Zerks (grease nipples).
Weight	4 oz (100 g)
Grease Gun Compatibility	Works with all grease gun types: pneumatic, manual and electric.
Seal	Durable nitrile rubber seal for longevity under high pressure.
Lock-on Mechanism	Four hardened spring steel jaws are resilient under high pressure.
Patents	WO 2011/069172